

Humidasduo HD-M2200

HD-M2200

Mobile type PTC steam humidifier available in 1.2 and 2.4 kg/h steam outputs. Gives hygienical, sterilized, odorless steam humidification suitable for human A/C system.

Terrific steam output among the industrial fields.



Features

- Mobile with wheels.
- It fills up 320 m³ by just 1 unit.
- •Use of high safety, long life PTC immersion heater. Has no cause for concern over fire breaking out even in the waterless operation.
- Air cleaning and sterilization capability by use of photocatalytic TiO2 (Titanium dioxide) filter and sterilization lamp.
- Eye-friendly display panel shows various messages.
- Easy, simplified operation with just one push of a button.
- No piping work needed, fitted with portable water tanks (10 ℓ tank×2). One time filling gives 8 hours continuous humidification.

Applications

- OfficesSchoolsPublic spacesHospitalsBeauty salons
- Art museums
 Electronic component plants, etc



Display space

UCAN Technology - Power of PTC immersion heater

No worry about fire breaking out even if in the waterless operation.

PTC immersion heater has self temperature controlled system which bundles the function of heater and thermostat. It has high-powered output in the water but little current flow in

the air by its self-controlled system. Resistivity of heater stays constant to a certain temperature, if the heater temperature rises over it, the resistivity will rise up rapidly (reach Curie point) and control the current flow.








Hospital

Standard Dimensions(mm)



Specifications

	Model		Humidasduo HD-M2200
	Steam output (kg / h)		L:1.2 H:2.4
	Power supply		1 ∮ 2W AC230V 50 / 60Hz
	Rated power (W)		L:1100 H:2100
	Rated current (A)		L:4.8 H:9.2
	Air volume at steam outlet port (MAX.)		30 m ³ / h
	Air volume for air cleaning and sterilization		30 m ³ / h
	Weight (kg)	Dry	24.5
		Full	44.5
	Water quality		Pure water
	Water tank capacity		10 Q×2
	Humidity setting		1099% RH
	Ambient condition		040°C (No freezing), Max.70%RH
	Safety equipment		Circuit breaker (ELB) to prevent overcurrent, Device to prevent waterless operation
	Auxiliary function		Output switch (L) & (H), Display for current relative humidity (%RH), Function for air cleaning, Function for air sterilization, Fault indications on display

Your best humidifier of confidence

® UCAN CO., LTD.

5-6-19 SANDA-CHO, HACHIOJI, TOKYO 193-0832, JAPAN URL http://www.ucan.co.jp/eng/ E-mail: ucan-information@ucan.co.jp TEL +81-42-665-8846 FAX +81-42-661-3887

Specifications are subject to change without notice. All UCAN trademarks and trade names are the property of UCAN CO.,LTD. All other trademarks and trade names are the property of their respective companies.



